


SPECIFICATION CONTROL DRAWING



D4921-XXX

NOTES:

- 1) MATERIAL: 6061-T6 ALUMINUM PER QQ-A-200/8 OR AMS-QQ-A-200/8 OR ASTM B221
MINIMUM TENSILE YIELD STRENGTH = 35 KSI
MINIMUM ULTIMATE TENSILE STRENGTH = 38 KSI
MINIMUM ELONGATION = 8%
- 2) FINISH: N/A
- 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
- 4) UNITS: INCHES UNLESS OTHERWISE NOTED
- 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
- 6) IDENTIFICATION: IDENTIFY WITH DART B/N USING FINE POINT PERMANENT INK MARKER
- 7) WEIGHT: 0.37 lbs/in
- 8) MANUFACTURED FROM SIGNATURE ALUMINUM, DIE# DAA-12
- 9) PART NUMBER IS D4921-XXX WHERE XXX IS CUT LENGTH IN INCHES (EX. D4921-108 IS 108" LONG)

RELEASED
2017-09-28
EEN 17-600

APPROVED

A	NEW ISSUE		VS	16.02.04
REV.	DESCRIPTION		BY	DATE
DESIGN	VS	DART AEROSPACE USA, INC. EUGENE, OR		
DRAWN	VS			
CHECKED	RF	DRAWING NO. D4921		REV. A
MFG. APPR.	DD			SHEET 1 OF 1
APPROVED	HS	TITLE LUG EXTRUSION		SCALE
DE APPR.	DS			NTS
DATE	16.02.04		COPYRIGHT © 2016 BY DART AEROSPACE USA, INC. THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE USA, INC.	